

## **Android Enterprise Smart Tablet**

# **ST103**

# Sleek Design with Compelling Enterprise Benefits





Android 10.x



**Performance** 

Octa-Core Processor



Wireless

Wifi, Bluetooth



**Battery** 

Long-lasting 6000mAh

environments.



Operating Temp.

-20°C to 50°C -4°F to 122°F



Camera

13MP Autofocus with flash (Optional)



Display

10.1"WXGA (1280 x 800)

#### **Enterprise Performance**

With adopting Qualcomm Snapdragon®, the best CPU for enterprise and Android 10, ST103 makes you do businessfaster and more securely, enhancing work efficiency.

## Long-lasting Battery

The energy-efficient processor combines with high capacity of 6000mAh, preserving the battery life to make sure it lasts the entire work shift and longer.

ST103 supports the fastest wireless connection of 802.11 a/b/g/n/ac/d/r/h/i/v/k/w to guarantee maximum speed and compatibility with WLAN, supporting 4GLTE

## Fast, Stable Connectivity

Slim, Trim, Light Design

Staying with consumer styling form factor as

well as enterprise features at the sametime,

allowing you to use in the customer-facing

as options.

## **Scratch Resistant Display**

10.1-inch multi-touch display is protected by Corning® Gorilla® Glass to provide exceptionally resistance to scratches and deep chips.

## **Optimized Efficiency in Field** Work

ST103 has adopted display that provides clear and bright visibility under outdoor conditions with auto-sensing glove, wet touch technology and stylus supporting uninterrupted productivity in work environment.

### **Markets and Applications**

#### Retail

- Customer Engagement
- Mobile Point-of-Sale (mPOS)
- Direct Store Delivery (DSD)
- Inventory Management
- · Line Busting

#### **Restaurant & Hospitality**

- Order Taking
- · Point of Sale (POS)

#### **Field Services**

- Work Order Management
- Asset Management

#### **FMCG**

- Merchandising
- Survey

#### Healthcare

- Point of Care
- Patient Record



## **Specifications**

PERFORMANCE CHARACTERISTICS		
СРИ	1.8 GHz Octa Core Processor	
os	Android 10 with GMS	
Memory	3GB RAM / 32GB Flash 4GB RAM / 64GB Flash (Optional)	
PHYSICAL CHAF	RACTERISTICS	
Dimension (L x W x D)	254.2 x 172.4 x 12.2 mm	
Weight	671g	
Display	10.1 inch, 1280 X 800 (WXGA)	
Imager Window	Corning® Gorilla® Glass	
Touch Panel	Capacitive multi-touch / Stylus	
Backlight	LED backlight	
Power	Integrated Battery 3.8V 6000mAh	
Expansion Slot	User accessible micro SDXC card slot (standard supports up to 2TB)	
SIM / SAM	1 Micro SIM (WWAN only)	
nterface	Docking Connector (10-pin) 1 x USB Type C (3.0) (OTG)	
Notification	Audible tone, Charging Status LED 1	
Voice & Audio	Speaker, Microphone	
Keypad	On-screen keypad	
WIRELESS WAN	DATA AND VOICE COMMUNICATION	
Radio Frequency Band	(Optional) Worldwide - LTE: 1(2100), 2(1900), 3(1800), 4(1700/2100), 5(850), 7(2600), 8(900), 20(800), 28(700) - WCDMA: B1, B2, B4, B5, B8 - GSM/EDGE: B2, B3, B5, B8  Japan	
	- LTE FDD : B1, B3, B8, B9, B19 - WCDMA : B1, B6, B8, B9	
GPS	(for WWAN only) A-GPS, GLONASS, BEIDOU, Galileo	

Radio	802.11 a/b/g/n/ac/d/r/h/i/v/k/w
Data Rate	5GHz: 802.11a/n/ac — up to 500 Mbps; 2.4GHz: 802.11b/g/n — up to 144 Mbps
Security and Encryption	WEP (40 or 104 bit); WPAWPA2 Personal (TKIP, and AES); WPAWPA2 Enterprise (TKIP, and AES) - EAPTTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PE APv0-MSCHAPv2, PE APv1-EAP-GTC, EAP Fast and LEAP
WIRELESS PAN	
Bluetooth	Bluetooth v5.0, BLE, Class 2
WIRED LAN	
Ethernet	Support (w/ Ethernet Cradle)
DATA CAPTURE	
Camera	(Optional) Rear – 13MP Autofocus Front – 5MP Fixed Focus
NFC	(Optional) ISO 14443 Type A & B ISO 15693, MiFare, Felica
SENSOR	
ight Sensor	Ambient Light
Motion Sensor	Accelerometer, E-Compass, Gyro
JSER ENVIRON	MENT
Operating Temp.	-20°C to 50°C / 4°F to 122°F
Storage Temp.	-20°C to 65°C / -22°F to +149°F
lumidity	90% non-condensing
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge
ACCESSORIES	
	1 slot charge / Ethernet cradle, Stylus, Screen protectors, Vehicle Charger, Vehicle mount

 $<sup>\</sup>label{eq:specifications} \mbox{\tt\# Specifications} \mbox{\tt are subject to change}.$